



Our corrugated conduit is flexible and flame retardant. It has excellent electrical and physical properties, including excellent acid fastness and corrosion resistance.

This product has the certifications below:



Colours Available:

■ Black

Material Specification:

Material: Polypropylene
Working Temperature: -40°C - +135°C
Self Extinguishing Class: UL94-V2
RoHS & REACH Compliant

| Part Number | ID | OD | Thickness | Reel Size |
|-------------|-------|------|-----------|-----------|
| CCC6.5BLACK | 6.5mm | 9mm | 0.25mm | 100M |
| CCC9.0BLACK | 9.0mm | 13mm | 0.25mm | 100M |
| CCC11BLACK | 11mm | 15mm | 0.25mm | 100M |
| CCC13BLACK | 13mm | 17mm | 0.27mm | 100M |
| CCC16BLACK | 16mm | 20mm | 0.27mm | 50M |
| CCC19BLACK | 19mm | 23mm | 0.27mm | 50M |
| CCC20BLACK | 20mm | 25mm | 0.30mm | 25M |
| CCC25BLACK | 25mm | 30mm | 0.30mm | 25M |
| CCC28BLACK | 28mm | 34mm | 0.35mm | 25M |
| CCC30BLACK | 30mm | 36mm | 0.35mm | 25M |
| CCC32BLACK | 32mm | 38mm | 0.35mm | 25M |
| CCC35BLACK | 35mm | 40mm | 0.35mm | 25M |

C TIE

Unit 5, Axiom Business Park,
41 Balcombe Road, Horley, Surrey, RH6 7HF
Tel: 01737 760645 Fax: 01737 760946
E-mail: sales@ctie.co.uk