



High quality crimp terminals with an adhesive heat shrink insulation. Ideal for applications where a waterproof termination is required including electrical equipment and auto electrical repairs.

Material (Insulation): High Density Polyethylene
Adhesive Lined: Yes
Material (Terminal): Brass with electro tin plating
Max. Operating Temperature: 125°C
Minimum Shrink Temperature: 120°C
Maximum Electrical Rating – 600V
Shrink Ratio: 3:1

Part Number	Insulation Colour	Insulation Type	Wire Size	Stud Size	Pack Size
T1POF47508HS	Red	Part Insulated	0.5mm ² -1.5mm ²	4.75x0.8mm	100
T1POFTI47508HS	Red	Fully Insulated	0.5mm ² -1.5mm ²	4.75x0.8mm	100
T1POF63508HS	Red	Part Insulated	0.5mm ² -1.5mm ²	6.35x0.8mm	100
T1POFTI63508HS	Red	Fully Insulated	0.5mm ² -1.5mm ²	6.35x0.8mm	100
T2POF47508HS	Blue	Part Insulated	1.5mm ² -2.5mm ²	4.75x0.8mm	100
T2POFTI47508HS	Blue	Fully Insulated	1.5mm ² -2.5mm ²	4.75x0.8mm	100
T2POF63508HS	Blue	Part Insulated	1.5mm ² -2.5mm ²	6.35x0.8mm	100
T2POFTI63508HS	Blue	Fully Insulated	1.5mm ² -2.5mm ²	6.35x0.8mm	100
T3POF63508HS	Yellow	Part Insulated	4mm ² -6mm ²	6.35x0.8mm	100
T3POFTI63508HS	Yellow	Fully Insulated	4mm ² -6mm ²	6.35x0.8mm	100

C TIE

Unit 5, Axiom Business Park,
41 Balcombe Road, Horley, Surrey, RH6 7HF
Tel: 01737 760645 Fax: 01737 760946
E-mail: sales@ctie.co.uk