



*Our corrugated conduit is flexible and flame retardant. It has excellent electrical and physical properties, including excellent acid fastness and corrosion resistance.*

This product has the certifications below:



Colours Available:

■ Black

Material Specification:

Material: Polypropylene  
Working Temperature: -40°C - +135°C  
Self Extinguishing Class: UL94-V2  
RoHS & REACH Compliant

Part Number	ID	OD	Thickness	Reel Size
CSC6.5BLACK	6.5mm	9mm	0.25mm	100M
CSC9.0BLACK	9.0mm	13mm	0.25mm	100M
CSC11BLACK	11mm	15mm	0.25mm	100M
CSC13BLACK	13mm	17mm	0.27mm	100M
CSC16BLACK	16mm	20mm	0.27mm	50M
CSC19BLACK	19mm	23mm	0.27mm	50M
CSC20BLACK	20mm	25mm	0.30mm	25M
CSC25BLACK	25mm	30mm	0.30mm	25M
CSC28BLACK	28mm	34mm	0.35mm	25M
CSC30BLACK	30mm	36mm	0.35mm	25M
CSC32BLACK	32mm	38mm	0.35mm	25M
CSC35BLACK	35mm	40mm	0.35mm	25M

**C TIE**

Unit 5, Axiom Business Park,  
41 Balcombe Road, Horley, Surrey, RH6 7HF  
Tel: 01737 760645 Fax: 01737 760946  
E-mail: sales@ctie.co.uk