



Our PVC sleeving is flexible and flame retardant. It has excellent electrical and physical properties, including excellent acid fastness and corrosion resistance.

This product has the certifications below:



Colours Available:

■ Black

Material Specification:

Material: PVC  
Working Temperature: -50°C - +105°C  
Flammability Rating: VW-1  
RoHS & REACH Compliant

Part Number	Size (ID)	Wall Thickness	Reel Size
CVPC2+COLOUR	2mm	0.5mm	200M
CPVC3+COLOUR	3mm	0.5mm	200M
CPVC4+COLOUR	4mm	0.5mm	200M
CPVC5BLACK	5mm	0.5mm	200M
CPVC6BLACK	6mm	0.5mm	100M
CPVC8BLACK	8mm	0.5mm	100M
CPVC10BLACK	10mm	0.5mm	100M
CPVC12BLACK	12mm	0.5mm	100M
CPVC14BLACK	14mm	0.5mm	100M
CPVC16BLACK	16mm	0.7mm	100M
CPVC20BLACK	20mm	0.75mm	100M
CPVC25BLACK	25mm	0.75mm	100M

**C TIE**

Unit 5, Axiom Business Park,  
41 Balcombe Road, Horley, Surrey, RH6 7HF  
Tel: 01737 760645 Fax: 01737 760946  
E-mail: sales@ctie.co.uk

All Specifications  
are Subject to  
change