



Our high quality expandable braided sleeve is flame-retardant and halogen-free. It offers durable abrasion resistance in a wide range of industrial applications. The open weave structure allows an easy installation on a bundle of hoses or cables, even with bulky or large size. Totally expanded sleeve can reach at least 1.5 times of the initial dimension. It is ideal for application in wire harness, automatic equipment, railway and general manufacturing industry where wire and cable are required to have a robust and durable protection.

This product has the certifications below:



Colours Available:

■ Black

Material Specification:

Material: Polyester
 Operating Temperature Range: -55°C - +150°C
 Flammability: VW-1
 RoHS and REACH compliant

Product Dimensions:

C Tie Part No	Size	Expandable Range		Reel Size
		Min	Max	
CEBS6B	6mm	3mm	9mm	100M
CEBS8B	8mm	5mm	16mm	100M
CEBS12B	12mm	8mm	24mm	50M
CEBS14B	14mm	9mm	26mm	50M
CEBS16B	16mm	10mm	27mm	50M
CEBS20B	20mm	14mm	30mm	50M
CEBS25B	25mm	18mm	35mm	50M
CEBS32B	32mm	20mm	50mm	50M
CEBS38B	38mm	30mm	60mm	50M
CEBS50B	50mm	40mm	80mm	25M

C TIE

Unit 5, Axiom Business Park,
 41 Balcombe Road, Horley, Surrey, RH6 7HF
 Tel: 01737 760645 Fax: 01737 760946
 E-mail: sales@ctie.co.uk

All Specifications are Subject to change