



High quality crimp terminals with an adhesive heat shrink insulation. Ideal for applications where a waterproof termination is required including electrical equipment and auto electrical repairs.

Material (Insulation): High Density Polyethylene
Adhesive Lined: Yes
Material (Terminal): Copper with electro tin plating
Max. Operating Temperature: 125°C
Minimum Shrink Temperature: 120°C
Maximum Electrical Rating – 600V
Shrink Ratio: 3:1

Part Number	Insulation Colour	Wire Size	Stud Size	Pack Size
T1F4HS	Red	0.5mm ² -1.5mm ²	4.3mm	100
T1F5HS	Red	0.5mm ² -1.5mm ²	5.3mm	100
T2F4HS	Blue	1.5mm ² -2.5mm ²	4.3mm	100
T2F5HS	Blue	1.5mm ² -2.5mm ²	5.3mm	100
T3F4HS	Yellow	4mm ² -6mm ²	4.3mm	100
T3F5HS	Yellow	4mm ² -6mm ²	5.3mm	100
T3F6HS	Yellow	4mm ² -6mm ²	6.4mm	100

C TIE

Unit 5, Axiom Business Park,
41 Balcombe Road, Horley, Surrey, RH6 7HF
Tel: 01737 760645 Fax: 01737 760946
E-mail: sales@ctie.co.uk