



High quality crimp terminals with an adhesive heat shrink insulation. Ideal for applications where a waterproof termination is required including electrical equipment and auto electrical repairs.

Material (Insulation): High Density Polyethylene
 Adhesive Lined: Yes
 Material (Terminal): Copper with electro tin plating
 Max. Operating Temperature: 125°C
 Minimum Shrink Temperature: 120°C
 Maximum Electrical Rating – 600V
 Shrink Ratio: 3:1

Part Number	Insulation Colour	Wire Size	Stud Size	Pack Size
T1R4HS	Red	0.5mm ² -1.5mm ²	4.3mm	100
T1R5HS	Red	0.5mm ² -1.5mm ²	5.3mm	100
T1R6HS	Red	0.5mm ² -1.5mm ²	6.4mm	100
T1R8HS	Red	0.5mm ² -1.5mm ²	8.4mm	100
T1R10HS	Red	0.5mm ² -1.5mm ²	10.5mm	100
T2R4HS	Blue	1.5mm ² -2.5mm ²	4.3mm	100
T2R5HS	Blue	1.5mm ² -2.5mm ²	5.4mm	100
T2R6HS	Blue	1.5mm ² -2.5mm ²	6.4mm	100
T2R8HS	Blue	1.5mm ² -2.5mm ²	8.4mm	100
T2R10HS	Blue	1.5mm ² -2.5mm ²	10.5mm	100
T2R12HS	Blue	1.5mm ² -2.5mm ²	13mm	100
T3R4HS	Yellow	4mm ² -6mm ²	4.3mm	100
T3R5HS	Yellow	4mm ² -6mm ²	5.3mm	100
T3R6HS	Yellow	4mm ² -6mm ²	6.4mm	100
T3R8HS	Yellow	4mm ² -6mm ²	8.4mm	100
T3R10HS	Yellow	4mm ² -6mm ²	10.5mm	100
T3R12HS	Yellow	4mm ² -6mm ²	13mm	100

C TIE

Unit 5, Axiom Business Park,
 41 Balcombe Road, Horley, Surrey, RH6 7HF
 Tel: 01737 760645 Fax: 01737 760946
 E-mail: sales@ctie.co.uk

All Specifications are Subject to change